

Analogic system

Internal hexagon Platform Large

Tightening torques and tools p. 140

Healing abutments



Titanium straight
healing abutment

TDKI-3
TDKI-5

h 3 mm
h 5 mm




Titanium countersunk
healing abutment

TSKI-3
TSKI-5


h 3 mm
h 5 mm

Impression components



Steel transfer for internal hexagon
implants platform LARGE
M2 Long fastening screw

SRKI
SP02



Steel transfer with impression cap
for Platform Normal internal
hexagon implants
Titanium fastening screw
Impression cap

TRKI-A
TP01
PC00



Titanium analogues



SAKI-5
SAKI-6







Abutments for cemented prosthesis


	Straight titanium abutment	TMKI
	Straight cylindrical titanium abutment	TMKIc
	Straight titanium abutment with shoulder, h 1-2-3 mm	TMKIb1 TMKIb2 TMKIb3
	Grade 2 titanium drillable inverted cone abutment	TMCRIK
	15-20 degrees titanium angled abutment	TMAKI15 TMAKI20

Bonding abutment for fastened prosthesis

	Cementation titanium abutments with shoulder 1-2 mm h	TMKIc-ce-SP1 TMKIc-ce-SP2 ce with hexagon	TMKIc-se-SP1 TMKIc-se-SP2 se without hexagon
	Aesthetic titanium base	TBKI-ce ce with hexagon	TBKI-se se without hexagon

Ucla abutments for fastened prosthesis

	Plastic cylinder with gold base	OUKI-ce ce with hexagon	OUKI-se se without hexagon
	Plastic cylinder with chromium cobalt base	CUKI-ce ce with hexagon	CUKI-se se without hexagon
	Plastic cylinder	RUKI-ce ce with hexagon	RUKI-se se without hexagon
	Castable plastic bar with steel knight connector	CAVAC BRC	steel knight connector castable plastic bar 55 mm length - ø 1,9 mm


	M2 titanium fastening screw	TP01	Every abutment comes with a screw. SKI-N driver required, see p. 139
---	-----------------------------	-------------	---

Analogic system

Internal hexagon Platform Large


Tightening torques and tools p. 140

Retaining system on ball attachments Ø 2,2 mm



Ø 2,2 mm ball titanium abutment
(TiN coating) with retaining cap

TMKI P2,2-0 h 3 mm h (shoulder) 0 mm
TMKI P2,2-2 h 4,4 mm h (shoulder) 2 mm
TMKI P2,2-3 h 5,4 mm h (shoulder) 3 mm
SKE-N p. 139 driver required



Steel housing cap
with Teflon

CA steel housing cap for Teflon caps
CNA orange Teflon cap (tender) 350 gr
060CRNAYDR8 yellow Teflon cap (extra soft) 500 gr
CNR pink Teflon cap (medium) 900 gr
CNV green Teflon cap (hard) 1300 gr
 To insert and remove the caps **485IC**
 insertor/extractor is required, see p. 138



Protective disk

DSP



Titanium retaining cap
for ball attachment

TC00-2,2 for ball Ø 2,2 mm



Steel analogue for modeling

SAN-P2,2 for attachment
with ball Ø 2,2 mm




Ø 2,2 mm ball attachment
transfer for tear-off impression
with variable cap

044CAI22

Internal hexagon Platform Large

Tightening torques and tools p. 140


TBase for CAD/CAM technology



LONG-LARGE titanium
aesthetic base
(Cutting rings at 4-6-8 mm, for fixation)

TBKI-LL-ce
ce with hexagon
for single prosthesis


TBKI-LL-se
se without hexagon
for multiple prosthesis



Titanium scanbody


SBKI

intra and extra oral use




M2 titanium fastening screw

TP01




Steel analogue
for 3D models

SAKI-5 (digital code IL50)
SAKI-6 (digital code IL60)
SKI 10/13R p. 138 driver required



M2 titanium fastening screw

TP01

Every abutment comes with a screw.
SKI-N  driver required, see p. 139

Also available on request titanium fastening screw with hexalobe engagement
for 20° inclined hole, and suited driver (max tightening torque 20 Ncm)

Extensive libraries are available for open CAD systems, 3Shape®, Exocad® and Dental Wings®.

- **TB** library for TBase in titanium for bonding
- **DIRECT** library for direct fastening connection

Connector Bridge Abutment


Internal hexagon Platform Large

Tightening torques and tools p. 140

Connectors and abutments



Titanium straight rotating conical abutment

COKI-D1,5 h 1,5 mm (plus 0,5 mm shoulder)
COKI-D3 h 3 mm (plus 0,5 mm shoulder)
DCD  p. 138 steel driver required



Titanium healing abutment, h 3,5 mm, for straight and angled connector, base \varnothing 5 mm

TSNC-3,5




Titanium conical rotating abutment, h 3,5 mm, for straight and angled connector, base \varnothing 5 mm

TMNI-coni-A
 With M1,4 screw

Castable cylinder for rotating conical abutment

RUNCA



Castable cylinder for straight and angled connector, base \varnothing 5 mm

RUCA
 With M1,4 screw

Cobalt chrome base Ucla for straight and angled connector, base \varnothing 5 mm


CUNI/A
 With M1,4 screw



Titanium fastening screw

M1,4 fastening screw between abutment and connector

Impression components



Steel transfer for straight and angled connector, base \varnothing 5 mm

SRCE

M1,4 long fastening screw for transfer

SP1,4




Steel analogue for straight and angled connector, base \varnothing 5 mm

SAN-K



TB Digital system


TBase for CAD/CAM technology



Aesthetic rotating conical base
LONG for straight and angled
connector, base \varnothing 5 mm


TB-coni-L
With M1,4 screw

For 10° inclined hole, 5,5 mm single cutting height with special screw available on request and dedicated screwdriver
For 20° inclined hole, 5,5 mm single cutting height with special screw available on request and dedicated screwdriver



Titanium rotating conical Scanbody
for straight and angled connector,
base \varnothing 5 mm

SBNI-coni-A
With M1,4 screw



Steel analogue for straight and
angled connector, base \varnothing 5 mm

SAN-K for 3D model
(CN5)
SKI 10/13R p. 138 driver required

C. B. A. Large

Extensive libraries are available for open CAD systems, 3Shape®, Exocad® and Dental Wings®.

- **TB** library for TBase in titanium for bonding
- **DIRECT** library for direct fastening connection